



PL

Bomba de pequeñas dimensiones.
Caudal constante regulable manualmente.
Esta bomba es de diafragma activado por solenoide.
El diafragma es la única pieza móvil.
Incorpora válvulas de Vitón.
Equipadas con tubos y accesorios para conexiones de aspiración e impulsión.
Voltage 230V 50/60Hz.

■ **Serie PL:**

El potenciómetro de regulación de caudal está marcado con doble escala seleccionable por conmutador. La escala azul para regulación de 0 a 100%. La escala roja es de más precisión para regulación de de 0 a 20%.

■ **Serie Kit Pool Ph/Rx:**

Kit para control de PH y Redox (Rx) para piscinas domésticas. La bomba peristáltica monitoriza en todo momento el nivel de Ph o de Redox en la piscina, ajustando la frecuencia de bombeo a la necesidad requerida.



Kit Pool

*A small pump.
Constant flow regulable by hand.
This pump has a solenoid operated diaphragm, which is the only moving part.
Viton valves.
Fitted with pipes and accessories for suction and drive connections.
Voltage 230V 50/60Hz.*

■ **PL series:**

*The flow regulation potentiometer is marked with a double scale that can be selected by a switch.
The blue scale for regulation from 0 to 100%. The red scale is for more precision for regulation from 0 to 22%.*

■ **Ph/Rx Pool kit series:**

Kit of pump and accessories to control the PH or Rx for domestic pools. The peristaltic pump controls all the time the PH or Rx values, and adjust the pumping frequency to obtain the requested value.

Tipo Type	Pot. Abs. Watt	Volt.	A	Caudal máx. Max. Flow lts./h.	Presion máx. Max. Pressure bar	N.º Impulsos x min.	Alt. Asp. Suction Height
PL 23	40	II 230	0,18	5	7	100	2
PL 50	75	II 230	1,1	10	5	110	2
PL 75	140	II 230	2	20	5	160	2

Tipo Type	Pot. Abs. Watt	Caudal máx. Max. Flow lts./h.	Presion máx. Max. Pressure bar	Regulación Regulation PH	Regulación Regulation Redox (Rx)
Kit Pool Ph	15	1,5	1,5	5 - 9	-
Kit Pool Rx	15	1,5	1,5	-	300 - 900 mV